



TECHNICAL REQUIREMENTS:

1. ELECTRICAL:

- CURRENT RATING: 3AMPS.
- VOLTAGE RATING: 500VAC.
- CONTACT RESISTANCE: 30mΩ MAX.
- INSULATION RESISTANCE: 1000mΩ

2. ENVIRONMENTAL:

- OPERATING TEMPERATURE: -25°C to +85°C
- STORAGE TEMPERATURE: 20°C TO 25°C

SCREW	2	Steel, Ni PLATING OVER ALL.	⑦
FISH FORK	2	SPCC, Tin PLATING OVER ALL.	⑥
SHELL	1	SPCC, Ni PLATING OVER ALL.	⑤
RIVET	2	COPPER ALLOY, Ni PLATING OVER ALL.	④
COVER	1	PA66+30%G. F	③
CONTACT	24	BRASS, SEMI-GOLD TIN	②
INSULATOR	1	PBT+30%G. F	①
PART NAME	QTY.	MATERIAL	ITEM

版本	變更內容	日期
千川	MODIFIXATION	DATE

 東莞市千川電子有限公司
DONG GUAN QIAN CHUAN ELECTRONIC CO., LTD

公差	數量	制圖	潘富國	品名	DV124+5 母座 卧式DIP (满信号针) 短柱铆合 锁螺丝		
TOLERANCE	QUANTITY	DRAWING	潘富國	TITLE			
.X ± 0.35	單位	CHECKED	LJ	料號	QDV5CN3-01PW1P9		
.XX ± 0.25	mm	APPROVE	LGL	材質			
.XXX ± 0.15	比例	角法	⊕ □	MATERIAL			
X° ± 3°	SCALE	PROJ.		頁數	1 OF 1	顏色	
.X° ± 1.5°	圖幅			SHEET		COLOR	
	SIZE						