



TECHNICAL REQUIREMENTS:

1. ELECTRICAL CHARACTERISTICS:
 - 1.1 CONTACT RESISTANCE: 30mΩ MAXIMUM
 - 1.2 CONTACT CURRENT RATING: 1.5A
 - 1.3 DIELECTRIC WITHSTANDING VOLTAGE: 500 V R. M. S.
 - 1.4 INSULATION RESISTANCE 1000 MEGOHMS MIN
 - 1.5 OPERATING TEMPERATURE: -40° C ~ 85° C
2. MECHANICAL CHARACTERISTICS:
 - 2.1 MATING FORCE: 35N MAX
 - 2.2 UNMATED FORCE: 10N MIN
8N Min After Durability
 - 2.3 DURABILITY: MANDATORY: 1500 CYCLES

1	HOUSING	HIGH TEMPERATURE PLASTIC UL94V-0	③
8	CONTACT	COPPER ALLOY, GOLD FLASH PLATED ON CONTACT AREA TIN PLATING ON SOLDER AREA, NI PLATING UNDER OVER ALL	②
1	SHELL	SPCC/BRASS ,Ni PLATING OVER ALL.	①
QTY'S	PART	SPECIFICATION	ITEM

版本 千川	變更內容 MODIFICATION	日期 DATE
00	新整理	2020.11.15

東莞市千川電子有限公司
DONG GUAN QIAN CHUAN ELECTRONIC CO., LTD

公差 TOLERANCE	數量 QUANTITY	制圖 DRAW IN	潘紅國	品名 TITLE	USB2.0 8Pin 母座 双层卧式DIP 大弯角 L=17.0mm		
.X ± 0.38	單位 UNIT	審核 CHECKED	TOMS	料號 PART NO.	QU2F08B1-GFSN0P9		
.XX ± 0.25	比例 SCALE	核准 APPROVE	LHL	材質 MATERIAL	圖號 DRAW NO.		
.XXX ± 0.10	圖幅 SIZE	角法 PROJ.		頁數 SHEET	1 OF 1	顏色 COLOR	
X° ± 2°							
.X° ± --							