



TECHNICAL REQUIREMENTS:

1. ELECTRICAL:

CURRENT RATING: 3AMPS.
 VOLTAGE RATING: 500VAC.
 CONTACT RESISTANCE: 30mΩ MAX.
 INSULATION RESISTANCE: 1000mΩ

2. ENVIRONMENTAL:

OPERATING TEMPERATURE: -25°C to +85°C
 STORAGE TEMPERATURE: 20°C TO 25°C

SCREW	2	Steel, Ni PLATING OVER ALL.	⑦
FISH FORK	2	SPCC, Tin PLATING OVER ALL.	⑥
SHELL	1	SPCC, Ni PLATING OVER ALL.	⑤
RIVET	2	COPPER ALLOY, Ni PLATING OVER ALL.	④
COVER	1	PA66+30%G. F	③
CONTACT	24	BRASS, SEMI-GOLD TIN	②
INSULATOR	1	PBT+30%G. F	①
PART NAME	QTY.	MATERIAL	ITEM

版本	變更內容	日期
千川	MODIFICATION	DATE
00	新整理	2016. 05. 30



公差	數量	制圖	潘红国	品名	DVI24+5 母座 卧式DIP (空信号针) 短柱铆合 锁螺丝		
TOLERANCE	QUANTITY	DRAWING	潘红国	TITLE			
.X ± 0.30	單位	審核	覃陆燕	料號	QDV5CN1-01PW1P		
.XX ± 0.25	UNIT	CHECKED	覃陆燕	PART NO.			
.XXX ± 0.20	比例	核准	李国亮	材質			
X° ± 2°	SCALE	APPROVE	李国亮	MATERIAL	图号	A068	
.X° ± --	圖幅	角法	李国亮	SHEET	顏色		
	SIZE	PROJ.	李国亮	頁數	1 OF 1		