



TECHNICAL REQUIREMENTS:

- ELECTRICAL CHARACTERISTICS:
 - CONTACT RESISTANCE: 30mΩ MAXIMUM
 - CONTACT CURRENT RATING: 1.5A
 - DIELECTRIC WITHSTANDING VOLTAGE: 500 V R. M. S.
 - INSULATION RESISTANCE 1000 MEGOHMS MIN
 - OPERATING TEMPERATURE: -40° C ~ 85° C
- MECHANICAL CHARACTERISTICS:
 - MATING FORCE: 35N MAX
 - UNMATED FORCE: 10N MIN
 - DURABILITY: MANDATORY: 5000 CYCLES

QTY'S	PART	SPECIFICATION	ITEM
1	HOUSING	HIGH TEMPERATURE PLASTIC UL94V-0	③
9	CONTACT	COPPER ALLOY, GOLD FLASH PLATED ON CONTACT AREA TIN PLATING ON SOLDER AREA, NI PLATING UNDER OVER ALL	②
1	SHELL	SPCC/BRASS , Ni PLATING OVER ALL.	①

版本	變更內容	日期
千川	MODIFIXATION	DATE
00	新整理	2016.06.25

 東莞市千川电子有限公司
DONG GUAN QIAN CHUAN ELECTRONIC CO., LTD

公差	數量	制圖	潘紅國	品名	USB3.0 9Pin 母座 卧式SMT式 外壳鱼叉脚 短体L=14.45mm		
TOLERANCE	QUANTITY	DRAWING	審核	TITLE			
.X ± 0.30	單位	mm	丁寅	料號	QU3F9C1-GFBN0P31		
.XX ± 0.20	比例	1:1	核准	李國亮	材質	圖號	
.XXX ± 0.10	SCALE		角法	⊕	MATERIAL	DRAW NO.	
X° ± 2°	圖幅	A4	PRUJ.	⊕	頁數	1 OF 1	顏色
.X° ± --	SIZE				SHEET		COLOR